

Product No: 271825

STAHL 6409/4128-5103-162-2220-22-850011 EMERGENCY LUMINAIRE WITH LED GRP 271825

FEATURES

- Emergency luminaire with LED GRP
- Voltage range: 110.00 240.00 VAC
- Equipped with a gas-tight NiCd battery (6 V, 7.0 Ah)
- Power consumption: 45 W
- Light output: 5810 lm with a neutral white color
- Efficiency: 129 lm/W
- Beam angle: 120 ° x 120 ° with diffusing glass
- Emergency lighting operation duration: 1.5 hours
- Operating temperature range: -30 °C to +50 °C



General Information

Brand	STAHL
Product Type	Emergency
Series	6409/4

Technical Attributes

Application	Application range (zones) - 2, 21, 22
Battery Size	6V, 7.0Ah
Lamp Wattage (W)	25
No. of Lamps	1
Nominal Power (W)	25
Rated Frequency (Hz)	50 - 60
Rated Maximum Operational Voltage AC (V)	230
Rated Minimum Operational Voltage AC (V)	110
Rated Operational Voltage AC (V)	110 - 240

Physical Attributes

Ambient Temperature Range (°C)	-30 to +55
Cable Type	Finely stranded, solid
Enclosure Material	Polyester resin, Glass fibre reinforced

Lamp Type	LED
LED Colour	Neutral White
Maximum Temperature (°C)	50
Minimum Temperature (°C)	-30
Mounting Type	Surface

Dimensions

Cable Cross Section (mm ²)	4 - 6
Dimensions (mm)	183.5W x 125H x 857D

Protection & Standards

Certifications	IECEX, ATEX
Degree of Protection	IP66/67
Standards and Approvals	ATEX/IECeX

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------