

Product No: HS6B-03B01

IDEC SAFTY INTERLOCK 3NC 1m CABLE SAFETY_SWITCH HS6B-03B01

FEATURES

- Integral molded cable reduces wiring time
- watertight sealing (contact is sealed; housing allows drainage)
- Direct Opening Action: Opening the door forces the contacts to disconnect even if the contacts are welded
- (IEC/ENC60947-5-1)
- Keys comply with ISO14119 and EN1088
- B10d: 2.0E+06



| General Information | |
|---------------------|-------------------------|
| Brand | IDEC |
| Product Type | Safety Interlock Switch |

| Technical Attributes | |
|---------------------------------|--------|
| Contacts | 3 |
| Minimum Electrical Life | 100000 |
| Minimum Mechanical Life | 100000 |
| Rated Insulation Voltage (V) | 300 |
| Rated Thermal Current - Ith (A) | 2.5 |

| Physical Attributes | |
|------------------------------------|-----------|
| Housing Colour | Black |
| Operational Temperature Range (°C) | -25 to 70 |

| Dimensions | |
|------------------|-----------------|
| Cable Length (m) | 1 |
| Dimensions (mm) | 30W x 15H x 78D |
| Weight (g) | 120 |



| Protection & Standards | |
|------------------------|------|
| Degree of Protection | IP67 |
| Pollution Degree | 3 |

Resources

Product catalogue (Flipbook)

Download from here