

Product No: DRM2P255

DEHN DEHNRail M SURGE ARRESTER DRM2P255

FEATURES

- Modular and pluggable two-pole
- Width: 1 module
- Fault indication
- Type 3 SPD according to EN 61643-11
- Energy-coordinated according to IEC 62305-4



General Information

Article No.	953200
Brand	DEHN
Product Type	Surge Protection Device

Technical Attributes

Circuit Type	Final Sub Circuit
Integral Fuse	No
Maximum Continuous Operating Voltage MCOV AC (V)	255
Maximum Continuous Operating Voltage MCOV DC (V)	255
No. of Poles	2P+PE
Nominal Discharge Current (8/20 μ s) - I _n (kA)	3
Nominal Load Current AC - I _n (A)	25
Nominal Voltage AC (V)	230
Operating State/Fault Indication	Green/Red
Response Time (ns)	≤ 25 (L-N) / ≤ 100 (L/N-PE)
Short-Circuit Withstand Capability - I _{sc} (kArms)	6
Signal C/O Contact	No
Total Discharge Current (8/20 μ s) - I _{total} (kA)	5 (L+N-PE)
Voltage Protection Level - U _p (kV)	≤ 1.25 (L-N) / ≤ 1.5 (L/N-PE)

Physical Attributes

Mounting Type	DIN Rail
---------------	----------

Dimensions

Dimensions (mm)	0.08W x 0.11L x 0.02D
No. of Modules	1
Weight (kg)	0.09

Protection & Standards

Degree of Protection	IP20
----------------------	------

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------