

## MERSEN DIN HV BACK UP FUSE-LINK, 24kV 50A 442x45mm, C/W 80N MEDIUM STRIKER 45DB240V50P

45DB240V50P



### GENERAL INFORMATION

|              |              |
|--------------|--------------|
| Brand        | MERSEN       |
| Product Type | HV Fuse Link |

### TECHNICAL ATTRIBUTES

|  |                      |
|--|----------------------|
| Breaking Capacity AC (kA)                                      | 63                   |
| Clearing I <sup>2</sup> t at Rated Voltage (kA <sup>2</sup> s) | 50                   |
| Contact Material   | Silver-Plated Copper |
| Indication   | Striker 80N          |
| Minimum Breaking Capacity (A)                                  | 205                  |
| Power Dissipation at I <sub>n</sub> (W)                        | 147                  |
| Rated Current (A)  | 50                   |
| Rated Voltage AC (V)   | 24000                |

### PHYSICAL ATTRIBUTES

|               |             |
|---------------|-------------|
| Body Style    | Cylindrical |
| Material      | Ceramic     |
| Mounting Type | Clip        |

### DIMENSIONS

|                |            |
|----------------|------------|
| Fuse Size (mm) | 56D x 442L |
| Weight (kg)    | 2.3        |

**PROTECTION & STANDARDS**

Standards and Approvals

IEC 60282-1, VDE 0670 part 4, DIN 43625

---