

Product No: 943 662-015

HIRSCHMANN 24V DC DIN RAIL POWER SUPPLY UNIT 943662015

FEATURES

- 24 V DC DIN rail power supply unit
- Power supply units can be connected in parallel
- 24 months of guarantee period



General Information

Brand	HIRSCHMANN
Product Type	Power Supply Unit
Series	RPS
Software Diagnostics	LED (power, DC ON)

Technical Attributes

Current Consumption (mA)	0.17
Electromagnetic Capability	10 V/m (80 MHz ... 2700 MHz)
Electrostatic Discharge (kV)	± 4 kV Contact Discharge; ± 8 kV Air Discharge
Input Voltage AC (V)	100-240
Input Voltage DC (V)	110-200
Maximum Nominal Output Voltage DC (V)	24
Operating Voltage Range	230V
Output Current (A)	0.63 at 24V DC
Output Voltage DC (V)	24-28
Rated Maximum Operational Voltage AC (V)	240
Rated Minimum Operational Voltage AC (V)	100
Rated Operational Voltage (V)	230
Resistance to Vibrations	Operating: 2 ... 500Hz 0,5m ² /s ³
Surge Voltage (kV)	Power Lines: 2 kV (Line/Earth), 1 kV (Line/Line)
Transition Type	2 kV Power Line

Physical Attributes

Maximum Temperature (°C)	70
Minimum Temperature (°C)	-10
Mounting Type	DIN Rail
Operational Temperature Range (°C)	-10 - 70
Relative Humidity	5-95 %
Storage Temperature Range (°C)	-40 - 85

Dimensions

Dimensions (mm)	22.5W x 75H x 91D
Weight (g)	130
Weight (kg)	0.13

Protection & Standards

Degree of Protection	IP20
Standards	CE

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------