

Product No: 460V15215M10K00312000

BD SENSORS LMK331 SCREW-IN TRA NSMITTER LMK331 SCREW-IN TRANSMITTER 460 V15215M10K00312000

FEATURES

- Pressure port G 3/4" flush for pasty and impurity media.
- Pressure port PVDF for aggressive media.



General Information	
Brand	BD SENSORS
Product Series	LMK 331
Product Type	Ceramic Sensor
Version	Standard

Technical Attributes	
Accuracy	0.5 % FSO
Application	Plant and machine engineering. Energy industry. Environmental engineering (water – sewage – recycling). Medical technology.
Electrical Connection	Male plug M12x1 (4-pin) / metal
Electrical Protection	Short-circuit protection: Permanent, Reverse polarity protection: No damage, but also no function, Electromagnetic compatibility: emission and immunity according to EN 61326.
Input Pressure (bar)	-11.5
Mechanical Connection	G3/4" DIN 3852 with flush sensor.
Mechanical Stability	Vibration: 10 g RMS (25 2000 Hz) according to DIN EN 60068-2-6. Shock: 500 g / 1 msec according to DIN EN 60068- 2-27.
Operational Life	100 million load cycles.
Output Signal	4 20 mA / 2-wire



Electronics / Environment: -40 ... 85 °C Storage: -40 ... 100 °C

Pressure Port	Stainless steel 1.4404 (316L)
Response Time (ms)	≤ 10
Seals	EPDM

Physical Attributes

Diaphragm Material

Ceramics Al2O3 96 %

Resources

Product catalogue (Flipbook)

Download from here