

Product No: HS5L-XD44M-G

IDEC INTERLOCK 2 CONTACTS SPRING LOCK HS5L-XD44M-G

FEATURES

- 1400N Locking Strength
- Gold-plated contacts suitable for small loads
- The head orientation can be rotated
- allowing 8 different actuator entries
- Applicable Standards: EN ISO14119
- GS-ET-19 (TUV approval)
- EN60947-5-1 (TUV approval)
- UL508 (UL Listing)
- CSA C22.2 No. 14 (c-UL listed)
- IEC60204-1/EN60204-1



General Information

Brand	IDEC
Product Type	Safety Interlock Switch

Technical Attributes

Contact Material	Gold Plated
Contacts	2
Minimum Electrical Life	100000
Minimum Mechanical Life	2000000
Rated Insulation Voltage (V)	250
Rated Thermal Current - I _{th} (A)	2.5

Physical Attributes

Operational Temperature Range (°C)	-25 to 55
------------------------------------	-----------

Dimensions

Dimensions (mm)	35W x 40H x 127D
Weight (g)	300

Protection & Standards

Degree of Protection	IP67
----------------------	------

Pollution Degree	3
------------------	---

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------