

Product No: 56604001C1322015000

BD SENSORS LMK382 STAINLESS STEEL PROBE LMK382 STAINLESS STEEL PROBE 56604001C1322015000

FEATURES

- Diameter 39.5 mm.
- Especially for sewage, viscous and pasty media.
- Robust and high overpressure capable.

General Information

Brand	BD SENSORS
Product Series	LMK 382
Product Type	Ceramic Sensor
Version	Standard

Technical Attributes

Application	Preferred areas of use are: Drinking water abstraction. Waste water treatment. Water recycling. Level monitoring in open tanks with low filling heights. Fuel storage. Tank farms / biogas plants.
Electrical Connection	PUR-cable (black, Ø 7.4 mm) [Shielded cable with integrated ventilation tube for atmospheric pressure reference].
Electrical Protection	Short-circuit protection: Permanent, Reverse polarity protection: No damage, but also no function, Electromagnetic compatibility: emission and immunity according to EN 61326.
Output Signal	4 ... 20 mA / 2-wire
Permissible Temperatures	Medium/ Electronics/ Environment/ Storage: -25 ... 125 °C
Pressure (mH ₂ O)	0.4
Response Time (ms)	Mean response time: ≤ 200 Max. response time: 380
Seals	EPDM

Physical Attributes

Diaphragm Material	Ceramics Al ₂ O ₃ 99.9 %
Housing Material	Stainless steel 1.4404 (316L)

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------