

## Product No: 220322

### STAHL TRANSMITTER SUPPLY UNIT 220322



#### General Information

Brand	STAHL
Product Type	Accessory

#### Technical Attributes

Analogue Signal - Current (mA)	Input / Output - 0/4 to 20
Application	Application range (zones) - 2
Communication	HART, 0.5 to 10 kHz
Connection Type	Screw Terminal
Maximum Current (A)	0.088
Maximum Power (mW)	576
Maximum Voltage (V)	27
No. of Channels	2
Nominal Voltage DC (V)	Auxiliary - 24
Power Consumption (W)	Auxiliary - 3.4
Power Loss (W)	Auxiliary - 2.8

#### Physical Attributes

Ambient Temperature Range (°C)	-20 to +70
Enclosure Material	Polyamide
LED Colour	Green - "PWR", Red - "LF"
Mounting Type	DIN Rail

## Dimensions

Cable Cross Section (mm <sup>2</sup> )	0.2 - 2.5
Dimensions (mm)	17.6W x 114.5H x 108D

## Protection & Standards

Certifications	IECEX, ATEX, Fmus, cFM
Degree of Protection	IP30, Terminals - IP20

## Resources

Product catalogue (Flipbook)	<a href="#">Download from here</a>
------------------------------	------------------------------------