

MERSEN DIN HV BACK UP FUSE-LINK, 12kV 6.3A 292x45mm, C/W 80N MEDIUM STRIKER 45DB120V6.3P

45DB120V6.3P



GENERAL INFORMATION

| | |
|--------------|--------------|
| Brand | MERSEN |
| Product Type | HV Fuse Link |

TECHNICAL ATTRIBUTES

| | |
|--|----------------------|
| Breaking Capacity AC (kA) | 63 |
| Clearing I ² t at Rated Voltage (kA ² s) | 1 |
| Contact Material | Silver-Plated Copper |
| Indication | Striker 80N |
| Minimum Breaking Capacity (A) | 30 |
| Power Dissipation at I _n (W) | 8 |
| Rated Current (A) | 6.3 |
| Rated Voltage AC (V) | 12000 |

PHYSICAL ATTRIBUTES

| | |
|---------------|-------------|
| Body Style | Cylindrical |
| Material | Ceramic |
| Mounting Type | Clip |

DIMENSIONS

| | |
|----------------|------------|
| Fuse Size (mm) | 56D x 292L |
| Weight (kg) | 1.7 |



PROTECTION & STANDARDS

Standards and Approvals

IEC 60282-1, VDE 0670 part 4, DIN 43625
