

Product No: GT3A-4AF20

IDEC PLUG-IN TIMER 11 PIN 100-240VAC DPDT GT3A-4AF20

FEATURES

- 4 selectable operation modes on each model
- External start, reset, and gate inputs
- Panel mount or socket mount
- Large variety of timing functions
- Power and output status indicating LEDs



General Information

Brand	IDEC
Product Type	Plug-In Timer
Series	GT3A

Technical Attributes

Contacts	Delayed DPDT
Input Voltage AC (V)	100 - 240
Input Voltage AC/DC (V)	24
Input Voltage DC (V)	12
Insulation Resistance (MΩ)	100
Maximum Reset Time (s)	60ms
No. of Pins	11
Output Voltage AC (V)	240
Output Voltage DC (V)	24
Power Consumption (W)	2.2VA (100V AC/60Hz), 4.1VA (200V AC/60Hz)
Timing Range	0.1s - 180hrs

Physical Attributes

Operational Temperature Range (°C)	-10 to +50
Storage Temperature (°C)	-30 - +70

Protection & Standards

Degree of Protection	IP40 (Timer), IP20 (Socket)
Pollution Degree	2
Standards and Approvals	EN 61812-1:2011, EN IEC 63000:2018

Resources

Product catalogue (Flipbook) [Download from here](#)