

Product No: 942 132-014

HIRSHMANN SPIDER III ST ANDRAD LINE, 6X 10/100/1000 BASE TX, RJ45 & 1X 100/1000 BASE FX SFP, 12-24 VDC 942132014

FEATURES

- Fanless design
- Store and forward switching mode
- Fast Ethernet



General Information

Brand	HIRSHMANN
Product Type	Unmanaged
Series	SPIDER III

Technical Attributes

Current Consumption (mA)	365 at 24VDC
No. of IGB Ports	7
No. of Ethernet Ports	6
No. of Fiber Ports	1
No. of Ports	6 x 10/100/1000BASE-T RJ45, 1 x 100/1000 SFP
Nominal Power (W)	8.7
Power Consumption (W)	8.7
Rated Maximum Operational Voltage DC (V)	32
Rated Minimum Operational Voltage DC (V)	9.6
Rated Operational Voltage DC (V)	12 - 24
Switch Type	Switch - Unmanaged

Physical Attributes

Maximum Temperature (°C)	60
Minimum Temperature (°C)	0
Mounting Type	DIN Rail / Wall
Operational Temperature Range (°C)	0 to +50

Dimensions

Dimensions (mm)	110H x 45W x 88D
-----------------	------------------

Protection & Standards

Degree of Protection	IP30
----------------------	------

Standards and Approvals	CE, FCC, EN61131, cUL61010-1/61010-2-201
-------------------------	--

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------