

## **Product No:130686**

## STAHL 8040/1180X-01L50SA05 CONTROL DEVICE SYSTEM CONSIG 8040 SERIES 130686

## **FEATURES**

- - Modular structure
- - Lightweight enclosure
- - Cable glands and entries 1 x M25, Ø 7 to 17 mm
- - Pushbutton
- - Without flange & plates
- - Suitable for shipping industry and offshore
- -Can be used in zones 1, 2, 21 and 22



General Information	
Brand	STAHL
Product Type	Control Device System

Technical Attributes	
Application	Application range (zones) - 1, 2, 21, 22
Contacts	NC/NO (Built-in element middle)
Maximum Continuous Voltage AC (V)	500
No. of Poles	2
Rated Operational Current (A)	10
Rated Operational Voltage AC (V)	550

Physical Attributes	
Ambient Temperature Range (°C)	-60 to +40
Enclosure Material	Polyester resin, Glass fibre reinforced
Maximum Temperature (°C)	40
Minimum Temperature (°C)	-60

Dimensions		
Cable Cross Section (mm²)	2.5	



Protection & Standards	
Certifications	IECEX, ATEX
Degree of Protection	IP66
Standards and Approvals	ATEX/IEC eX

Resources	
Product catalogue (Flipbook)	Download from here