

Product No: 942 070-999-002

HIRSCHMANN WIRELESS ACCESS POINT 942 070-999-002

FEATURES

- Wireless Access Point with IEEE 802.11n WLAN technology
- ComboPort Ethernet: 10/100/1000 Mbps via RJ45 or SFP
- Second Ethernet port: 10/100/1000 Mbps via RJ45
- Ruggedized design suitable for industrial environments
- Operating temperature range from -40 °C to +70 °C
- Part of the OpenBAT Series by Hirschmann
- Includes one fiber port and two 1GB Ethernet ports

General Information

Brand	HIRSCHMANN
Series	OpenBAT
Software Modules	WLAN Controller, Industrial HiVision, LANConfig

Technical Attributes

Communication Interface	V.24, USB
Connector Type	3× RP-SMA Female, 1xRP-SMA Male connector (for Antenna)
No. of 1GB Ports	2
No. of Ethernet Ports	1
No. of Fiber Ports	1
No. of Ports	1xEthernet ComboPort 10/100/1000 via RJ45 or SFP, 1xEthernet 10/100/1000 via RJ45
Power Consumption (W)	17.5 (Total Max.)
Rated Operational Voltage DC (V)	Power 1: 24-48, Power 2: 24-48

Physical Attributes

Housing Material	Metal
Maximum Temperature (°C)	70
Minimum Temperature (°C)	-40

Mounting Type	DIN Rail
Operational Temperature Range (°C)	+0 to +60

Dimensions

Dimensions (mm)	145Hx151Wx121D
Weight (kg)	1.5

Protection & Standards

Degree of Protection	IP20
----------------------	------

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------