

## Product No:101167057

### SCHMERSAL AZ 16 ZVRK-M16-2254 SAFETY SWITCH WITH SEPARATE ACTUATOR 101167057



#### General Information

Brand	SCHMERSAL
No. of Cable Glands	3

#### Technical Attributes

No. of Auxiliary Contacts	1
Switching Frequency	4000/h
Contact Material	Silver
Latching Force (N)	5
Maximum Actuating Speed (m/s)	2
Maximum Cable Cross Section (mm <sup>2</sup> )	2.5
Maximum Fuse Rating	6 A gG D-fuse
Maximum Storage Temperature (°C)	85
Minimum Cable Cross Section (mm <sup>2</sup> )	0.25
Minimum Mechanical Life	1000000 Operations
Minimum Storage Temperature (°C)	-40
No. of Safety Contacts	1
Positive Break Travel (mm)	8
Rated Impulse Withstand Voltage (kV)	6
Rated Insulation Voltage (V)	500
Rated Operational Current AC-15 (A)	Auxiliary Contacts - 4A, Safety Contacts - 4A
Rated Operational Current DC-13 (A)	Auxiliary Contacts - 4A, Safety Contacts - 4A
Rated Operational Voltage AC-15 (V)	230V AC

Rated Operational Voltage DC-13 (V)	24 VDC
Rated Short-circuit Current (A)	1000
Switching Element	NO Contact, NC Contact
Switching Principle	Slow Action, Positive Break NC Contact
Termination	Screw Terminals
Thermal Test Current (A)	10

### Physical Attributes

Cable Entry	3 x M16 x 1.5
Housing Material	Plastic, Glass-fibre Reinforced Thermoplastic, Self-extinguishing
Maximum Ambient Temperature (°C)	80
Minimum Ambient Temperature (°C)	-30

### Dimensions

Sensor Height (mm)	90
Sensor Length (mm)	30
Sensor Width (mm)	52

### Protection & Standards

Degree of Protection	IP67
Pollution Degree	3
Standards and Approvals	EN IEC 60947-5-1, EN ISO 13849-1

### Resources

Product catalogue (Flipbook)	<a href="#">Download from here</a>
------------------------------	------------------------------------