

Product No: SFM3-125-50-275

NOVARIS SURGE FILTER 3P+N+PE 50kA SFM3-125-50-275

FEATURES

- - Medium Current Filters
- - Percentage Active Display
- - Three Stages of Protection
- - All Mode Protection
- - Active Alarm



General Information

| | |
|--------------|--------------|
| Brand | NOVARIS |
| Product Type | Surge Filter |
| Series | SFM3 |

Technical Attributes

| | |
|---|-------------|
| Connection Type | Series |
| Lightning Impulse Current (10/350 μ s) - Iimp (kA) | 6.25 |
| Maximum Continuous Operating Voltage MCOV AC (V) | 275 (L-N) |
| Maximum Discharge Current (8/20 μ s) - I _{max} (kA) | 50 |
| Maximum Load Current - I _N (A) | 125 |
| No. of Phases | 3 |
| No. of Poles | 3P+N+PE |
| Nominal Discharge Current (8/20 μ s) - I _n (kA) | 20 |
| Nominal Voltage AC (V) | 230 |
| Voltage Protection Level (3kA 8/20 μ s) - U _p (kV) | <0.36 (L-N) |

Physical Attributes

| | |
|------------------------------------|-----------|
| Mounting Type | Panel |
| Operational Temperature Range (°C) | -40 to 70 |

Dimensions

| | |
|-----------------|--------------------|
| Dimensions (mm) | 450H x 390W x 190D |
|-----------------|--------------------|

Protection & Standards

Degree of Protection

IP20

Standards and Approvals

IEC 61643-11, AS/NZS 1768

Resources

Product catalogue (Flipbook)

[Download from here](#)

TECHNICAL DRAWING

