

## Product No: BXTML2BEHFS5

### DEHN BLITZDUCTOR XT COMBINED LIGHTNING CURRENT AND SURGE ARRESTER MOD BXTML2BEHFS5

#### FEATURES

- Space-saving combined lightning current and surge arrester module
- With LifeCheck feature for protecting one pair of high-frequency transmissions without galvanic isolation, with direct or indirect shield earthing
- LifeCheck detects thermal or electrical overload, this indicates arrester has to be replaced
- This status is indicated contactlessly by the DEHNrecord LC / SCM / MCM reader.



#### General Information

Brand	DEHN
Product Type	Surge Protection Device
Reference No.	920270
Suitable For	Pluggable DIN Rail Mounted

#### Technical Attributes

Earth Fault Protection	DIN rail (top hat rail)
Lightning Impulse Current (10/350 $\mu$ s) - I <sub>imp</sub> (kA)	9
Limiting Frequency (MHz)	100
Maximum Continuous Operating Voltage MCOV AC (V)	4.2
Maximum Continuous Operating Voltage MCOV DC (V)	6
Maximum Continuous Voltage AC (V)	4.2
Maximum Continuous Voltage DC (V)	6
Nominal Discharge Current (8/20 $\mu$ s) - I <sub>n</sub> (kA)	20
Nominal Load Current AC - I <sub>n</sub> (A)	1
Nominal Voltage (V)	5
Nominal Voltage DC (V)	5
SPD Type	2

line-line at 1 kV/ $\mu$ s C3 (UP)  $\leq$  11 V  
line-PG at 1 kV/ $\mu$ s C3 (UP)  $\leq$  11 V

Voltage Protection Level - Up (kV)	11
------------------------------------	----

### Physical Attributes

Colour	Yellow
Enclosure Material	Polyamide PA 6.6
Mounting Type	On Basic Element
Operational Temperature Range (°C)	-40 to 80

### Dimensions

Dimensions (mm)	12W x 45H x 51D
Weight (kg)	0.022

### Protection & Standards

Degree of Protection	IP20
Standards and Approvals	IEC 61643-21 / EN 61643-21

### Resources

Product catalogue (Flipbook)	<a href="#">Download from here</a>
------------------------------	------------------------------------