

Product No: CBLGEN03

RED LION CABLE - RS422/485 BARE WIRE CBLGEN03

FEATURES

- PID Controller with multiple DIN sizes: 1/4, 1/8, and 1/16
- Power Connection options: AC 100 to 240 VAC or DC 24 VDC
- Universal Input types including Temperature/RTD and various Thermocouple types (T, E, J, K, R, S, B, N, L, U, TXK)
- RTD Inputs compatible with 2 or 3 wire configurations and Excitation of 180 mA
- Process Inputs include ranges of 0-5VDC or 0-10VDC and current inputs of 0-20mA or 4-20mA
- Optional CT Input for single-phase AC current measurement (0 to 25 mA)
- Remote Input capability for voltage (0-10VDC) and current (0-20mA or 4-20mA)
- RS-485 serial communication interface
- Output options include Time proportioning or DC analog signals

General Information

Brand	RED LION
Product Type	Accessory
Series	PXU
Suitable For	Graphite Series, G3 Series

Technical Attributes

Communication	RS-422/485
Nominal Power (W)	5
Rated Minimum Operational Voltage DC (V)	24

Physical Attributes

Maximum Temperature (°C)	50
Minimum Temperature (°C)	0

Dimensions

Cable Length (m)	3.05
------------------	------

Protection & Standards

Degree of Protection	IP65
----------------------	------

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------
