

## Product No: 101127008

### SCHMERSAL IFL10-30L-1ITP-1766 INDUCTIVE PROXIMITY SWITCH 101127008

#### FEATURES

- Inductive proximity switch with a long design
- DC 4-wire connection
- Cylinder shape with ISO thread M30
- Sensing distance of 10 mm
- Equipped with both NO (Normally Open) and NC (Normally Closed) contacts
- Metal enclosure material for durability
- Operating voltage range from 10 to 60 VDC
- Maximum output current of 400 mA
- Switching frequency of up to 350 Hz



*Note: The membrane protects the button against grinding dust or other pasty, viscous substances.*

#### General Information

Brand	SCHMERSAL
Cable Note	All indications including the conductor ferrules.
EAN	4030660000000
eCl@ss Number, Version 11.0	27-27-01-01
eCl@ss Number, Version 9.0	27-27-26-01
ETIM 6.0	EC002714
ETIM 7.0	EC000030
Housing Construction Form	Norm construction design
Product Type	Proximity Switch
Protection Class of Operating Resource	3
Series	IFL
Working Principle	Mechanical

#### Technical Attributes

No. of Auxiliary Contacts	1
Contact Material	Silver

Maximum Cable Cross Section (mm <sup>2</sup> )	1.5
Maximum Fuse Rating	6 A gG D-fuse
Maximum Nominal Output Voltage DC (V)	1
Minimum Actuating Speed (mm/min)	160
Minimum Cable Cross Section (mm <sup>2</sup> )	0.34
Minimum Mechanical Life	10000000 Operations
Minimum Positive Break Force (N)	19
No. of Safety Contacts	1
Nominal Output Current (A)	0.2
Overvoltage Category	3
Rated Impulse Withstand Voltage (kV)	4
Rated Insulation Voltage (V)	400
Rated Maximum Operational Voltage DC (V)	60
Rated Minimum Operational Voltage DC (V)	10
Rated Operational Current (A)	0.2
Rated Short-circuit Current (A)	1000
Switching Element	3 NC contact
Switching Principle	Slow action
Terminal Type	Connector
Utilisation Category	DC-13   AC-15
Utilisation Category DC-13	0.05 A

Physical Attributes	
Actuator Type	Magnet
Enclosure Coating Material	Painted
Enclosure Material	Glass-fibre, reinforced thermoplastic
Gross Weight (g)	25
Installation Conditions	Not flush
Maximum Ambient Temperature (°C)	70
Maximum Temperature (°C)	110
Minimum Ambient Temperature (°C)	-30
Minimum Temperature (°C)	0

Mounting Type	Threaded
Net Weight (g)	341.67
Storage Temperature (°C)	-25 to 70
Wire Cross-Section	13 AWG

#### Dimensions

Height (mm)	14
Sensor Height (mm)	84
Sensor Length (mm)	46
Width (mm)	22.5

#### Protection & Standards

Degree of Protection	IP67
Pollution Degree	3
Standards	EN IEC 61496-1 / EN IEC 61496-2

#### Resources

Product catalogue (Flipbook)	<a href="#">Download from here</a>
------------------------------	------------------------------------