

# ABB E12N4ETG10W ACB E1.2N 4P 66KA WITHDRAWABLE 1000A EKIP TOUCH LSIG

E12N4ETG10W



## GENERAL INFORMATION

Brand	ABB
Product Type	Automatic
Version	Withdrawable

## TECHNICAL ATTRIBUTES

Breaking Capacity 415V AC - I <sub>cu</sub> (kA)	66
G (0.1 to 1 x I <sub>n</sub> ) - I <sub>4</sub> (A)	100-1000
I (1.5 to 15 x I <sub>n</sub> ) - I <sub>3</sub> (A)	1500-15000
L (0.4 to 1 x I <sub>n</sub> ) - I <sub>1</sub> (A)	400-1000
No. of Poles	4P
Power Loss (W)	156
Rated Current (A)	1000
Rated Impulse Withstand Voltage (kV)	12
Rated Insulation Voltage AC (V)	1000
Rated Operational Voltage AC (V)	690
Rated Short-time Withstand Current - I <sub>cw</sub> (kA/1s)	50
Rated Uninterrupted Current - I <sub>u</sub> (A)	1000
S (0.6 to 10 x I <sub>n</sub> ) - I <sub>2</sub> (A)	600-10000
Terminal Type	HR-HR
Trip Unit	EKIP Touch LSIG

## DIMENSIONS

Frame Size	E1.2
------------	------

---

## PROTECTION & STANDARDS

Standards and Approvals	IEC
-------------------------	-----

---

## RESOURCES

Product catalogue (Flipbook)	<a href="#">Download from here</a>
------------------------------	------------------------------------

---