

Product No: DVCII255

DEHN 1P 25kA IIMP 10/350USEC 255VAC 2 WIRE VEN CI C/W INT FUSE DVCII255

FEATURES

- Single-pole DEHNvenCI combined lightning current and surge arrester with integrated backup fuse
- Maximum availability due to RADAX FLOW follow current limitation
- Capable of protecting terminal equipment
- For protecting low-voltage consumer's installations against surges and even direct lightning strikes
- For installation in conformity with the lightning protection zone concept at the boundaries from 0A
- 2



General Information

Brand	DEHN
Product Type	Surge Protection Device
Reference No.	961200
Suitable For	Power Supply Systems

Technical Attributes

Follow Current Extinguishing Capability AC (kArms)	50
Lightning Impulse Current (10/350 μ s) - Iimp (kA)	25
Maximum Continuous Voltage AC (V)	255
No. of Poles	1
Nominal Voltage AC (V)	230

Physical Attributes

Enclosure Material	Thermoplastic
--------------------	---------------

Dimensions

Dimensions (mm)	72W x 150H x 36D
Weight (g)	477.3

Weight (kg)	0.432
-------------	-------

Protection & Standards

Degree of Protection	IP20
----------------------	------

Standards and Approvals	EN 61643-11
-------------------------	-------------

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------
