

Product No: XRG2-185/10-3P

ABB XRG2-185/10-3P SWITCH DISCONNECTOR FUSE XRG2-185/10-3P

FEATURES

- Easy, pre-engineered wire-free installation
- Simple removal and replace with plug-in contacts
- Fuse monitoring functionality (EFM)
- Up to 35% lower power losses
- Complies to standard IEC 60947-3



| General Information | |
|---------------------|-------------------|
| Brand | ABB |
| Product Type | Fuse Disconnector |
| Suitable For | NH2 |
| Туре | Main Switch |

| Technical Attributes | |
|--|-----------------|
| Main Circuit Electrical Connection | Bolt Connection |
| Maximum Operational Voltage AC (V) | 690 |
| No. of Poles | 3 |
| Position of Control Element | Front Side |
| Power Dissipation at In (W) | 100 |
| Rated Conditional Short-Circuit Current - Inc (kA) | 120 |
| Rated Current (A) | 400 |
| Rated Uninterrupted Current - Iu (A) | 400 |
| Rated Voltage AC (V) | 690 |
| | |

| Physical Attributes | |
|---------------------|-------------|
| Cable Entry | Side |
| Mounting Type | BusbarMount |

Dimensions



| Fixing Centres (mm) | 185 |
|---------------------|------|
| Fuse Size | NH2 |
| Thickness (mm) | 10 |
| Weight (kg) | 15.5 |

| Protection & Standards | |
|-------------------------|-------------|
| Degree of Protection | IP41 |
| Standards and Approvals | IEC 60947-3 |

| Resources | |
|------------------------------|--------------------|
| Product catalogue (Flipbook) | Download from here |