

## Product No: 68581753

### ABB ACS150 0.75KW 2.4A IP20 MICRO DRIVE ACS150-03E-02A4-4

#### FEATURES

- - Power range 0.37 to 4 kW/0.5 to 5 Hp
- - IP20 enclosure
- - Scalar control
- - Integrated user interface and potentiometer
- - Built-in brake chopper, EMC filter for second environment
- - Coated boards
- - Pre-defined connection macros



#### General Information

Brand	ABB
Product Type	Micro
Reference No.	ACS150-03E-02A4-4
Series	ACS150

#### Technical Attributes

No. of Analogue Inputs	1
No. of Digital Inputs	5
No. of Phases	3
No. of Relay Outputs	1
Output Current - Light Duty (A)	2.4
Output Current - Normal Duty (A)	2.4
Output Power - Light Duty (kW)	0.8
Output Power - Normal Duty (kW)	0.75
Rated Supply Voltage AC (V)	380 - 480

#### Physical Attributes

Ambient Temperature Range (°C)	-10 to 40 (No frost allowed)
Mounting Type	Cabinet

## Dimensions

Dimensions (mm)	239H x 70W x 142D
-----------------	-------------------

Size of Frame	R1
---------------	----

## Protection & Standards

Degree of Protection	IP20
----------------------	------

Standards and Approvals	UL, cUL, CE, RCM, RoHS and EAC
-------------------------	--------------------------------

## Resources

Product catalogue (Flipbook)	<a href="#">Download from here</a>
------------------------------	------------------------------------