

Product No: CD5.121

PULS DC/DC CONVERTER 12VDC 8A CD5.121

FEATURES

- 24V DC-input
- Isolated 12 V DC output
- Efficiency up to 88.2%
- Width only 32mm
- 20% Output power reserves
- Full power between -25°C and +60°C
- Soft-start function
- Minimal inrush current surge
- Reverse input polarity protection



General Information

Brand	PULS
Country of Origin	China / Czech Republic
Customs Tariff Number	85043121
E Classification	E-CS02
Product Type	DC/DC Converter
Range	DIMENSION
Series	C series
Warranty Period (Months)	36

Technical Attributes

Connection Type	Screw terminals
Derating	2.5 W/°C
Derating Temperature (°C)	> +60
Efficiency	88.20%
Input Voltage Range DC (V)	24
Integrated Decoupling Function	No
Maximum Ripple and Noise Voltage (mVpp)	75
Minimum Input Voltage DC (V)	24
Output Current Range (A)	8 - 6.4
Output Power (W)	96

Output Voltage (V)	12-15
Power Loss (W)	12.8
Power Reserve Type	Power Boost
Power Reserves	20%
Rated Current (A)	8
Special Application	Hazardous location, Marine
Use In Crosslinking	Yes

Physical Attributes

Conformal Coating	No
Mounting Type	DIN Rail
Operational Temperature Range (°C)	-25 to 70

Dimensions

Dimensions (mm)	32W x 124H x 102D
Weight (g)	425

Protection & Standards

Degree of Protection	IP20
Standards and Approvals	ATEX EN 60079, Class I Div. 2 Canada - CSA, Class I Div. 2 USA - CSA, Class I Div. 2 Canada - UL, Class I Div. 2 USA - UL, EU Declaration of Conformity, IECEx IEC 60079, IEC 60950 CB Scheme, Korea Certification, Marine ABS, Marine DNV, UL 508 Canada, UL 508 USA, UL 60950-1 Canada, UL 60950-1 USA, UK Declaration of Conformity

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------