

Product No: PSE60-600-70

ABB PSE60-600-70 SOFTSTARTER - 60 A - 208 ... 600 V AC PSE60-600-70

FEATURES

- Offers two-phase control with a smooth start and stop using voltage or torque ramps
- Built-in bypass for energy saving and easy installation
- Ensures reliable and secure motor performance with features such as kickstart, EOL and locked rotor protection
- User-friendly illuminated display with languageneutral symbols



| General Information | |
|---------------------|---------------|
| Brand | ABB |
| Product Type | General - PSE |

| Technical Attributes | |
|--|----------------|
| Actuating Voltage Type | AC |
| Display Screen | Yes |
| Function | Torque Control |
| IEC Rated Operational Power 400V - Heavy (kW) | 22 |
| IEC Rated Operational Power 400V - Normal (kW) | 30 |
| Overload Protection | Yes |
| Rated Control Supply Voltage AC (V) | 100 |
| Rated Current - Heavy Duty (A) | 45 |
| Rated Current - Medium Duty (A) | 60 |
| Rated Operational Current (A) | 60 |
| Rated Operational Power - In-Line Connection (230V) (kW) | 15 |
| Rated Operational Power - In-Line Connection (400V) (kW) | 30 |
| Rated Operational Voltage AC (V) | 208 |
| Rated Supply Voltage AC (V) | 100 |
| Release Class | Adjustable |



| Physical Attributes | |
|------------------------------------|------------|
| Operational Temperature Range (°C) | -25 to +60 |

| Dimensions | |
|-----------------|-------------------|
| Dimensions (mm) | 90W x 245H x 184D |
| Size of Frame | A |

| Protection & Standards | |
|---------------------------|-------|
| Degree of Protection | IP0 0 |
| NEMA Degree of Protection | 1 |

| Resources | |
|------------------------------|---------------------------|
| Product catalogue (Flipbook) | <u>Download from here</u> |