

Product No: DPIMD24M2S

DEHN DPIMD24M2S SPD T2 FOR SIGNALS AND MEASUREMENT EQUIP.

FEATURES

- - Energy-coordinated two-stage arrester
- - No leakage currents to earth
- - Suitable for three shielding concepts
- - Easy to mount due to two-part design
- - Standards IEC/EN 61643-21



General Information

Article No.	929941
Brand	DEHN
Product Type	Signal Line Protector

Technical Attributes

Lightning Impulse Current (10/350 μ s) - Iimp (kA)	1 (Per Line)
Maximum Continuous Operating Voltage MCOV AC (V)	24.5
Maximum Continuous Operating Voltage MCOV DC (V)	34.8
Nominal Discharge Current (8/20 μ s) - In (kA)	10 (Per Line)
Nominal Voltage (V)	24
Thread Size	M20 x 1.5 (F-M)
Total Discharge Current (8/20 μ s) - Itotal (kA)	10
Voltage Protection Level - Up (kV)	≤ 0.065 (Line-Line)/ ≤ 0.65 (Line-PG)

Physical Attributes

Enclosure Material	Stainless steel (V2A)
--------------------	-----------------------

Protection & Standards

Degree of Protection	IP67
----------------------	------

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------