

## Product No: 205686

### STAHL 8146/5-VII-305-00-0010-K LOAD DISCONNECT SWITCH 205686

#### FEATURES

- Load disconnect switch with 3-pole + N configuration
- Rated at 16.000 A (T6) for operational current
- Short-circuit protection rated at a maximum of 25 A with gG fuse
- Operating temperature range from -40 °C to +51 °C
- IP66 rated for dust and water resistance
- Features a red handle with a yellow protective collar
- Constructed from Polyester resin material
- Part of the 8146/5 Series by Stahl brand
- Designed for panel mounting



#### General Information

Brand	STAHL
Product Type	Load Disconnecter
Series	8146/5

#### Technical Attributes

Application	Application range (zones) - 1, 2, 21, 22
Fuse Type	gG
No. of Poles	3
Nominal Output Current (A)	40
Rated Frequency (Hz)	50 - 60
Rated Operational Current (A)	40

#### Physical Attributes

Ambient Temperature Range (°C)	-40 to +48
Enclosure Material	Polyester, Glass fibre reinforced
Handle Colour	Black shroud and handle
Maximum Temperature (°C)	51

Mounting Type

Panel

### Dimensions

Dimensions (mm)

176.5W x 340.5H x 170D

### Protection & Standards

Certifications

European Union (ATEX), IECEx

Degree of Protection

IP66

Standards and Approvals

ATEX/IECEx

### Resources

Product catalogue (Flipbook)

[Download from here](#)