

## ABB RCBO, 10kA 3P+N 50A C-CURVE 30mA DSE203NMC50A30

DSE203NMC50A30

### FEATURES

- Protection against short circuit, thermal overload and earth leakage
- Functional earth white cable to give additional protection in case of loss of the neutral
- Earth fault trip indicator window
- Real contact position indicator on toggle
- Flying leads for installation in chassis distribution boards
- Pole configuration 3P+N



### GENERAL INFORMATION

Brand	ABB
Product Type	RCBO
Series	DSE200

### TECHNICAL ATTRIBUTES

Breaking Capacity 415V AC - Icu (kA)	10
Curve Type	C Curve
No. of Poles	3P+N
Operational Temperature Range (°C)	-25 to +70
Rated Current (A)	50
Rated Frequency (Hz)	50/60
Rated Impulse Withstand Voltage (kV)	4
Rated Insulation Voltage AC (V)	500
Rated Operational Voltage AC (V)	415
Rated Residual Current (mA)	30
Terminal Type	Pillar terminals
Type of Residual Current	A

### DIMENSIONS

Dimensions (mm)	53.4Wx117.5Hx71.6D
-----------------	--------------------

### PROTECTION & STANDARDS

Degree of Protection	IP40 (Housing), IP20 (Terminals)
----------------------	----------------------------------