

Product No: IC200ALG630

EMERSON VERSAMAX ANALOG INPUT MODULE, 16 BIT THERMOCOUPLE, 7 CHANNEL IC200ALG630

FEATURES

- Channel Density: 4 channels
- Input Type: RTD (Resistance Temperature Detector)
- Resolution: 16-bit accuracy
- Communication Protocols Supported: PROFINET, PROFIBUS DP, Modbus/TCP, Ethernet Global Data (EGD), DeviceNet, GENIUS
- Media Connectors Available: 2x RJ45 or 2x ST connectors
- Applications Include: Machine Control, Light Process Control, General Automation
- Mounting Type: DIN rail mounted

General Information	
Brand	EMERSON
Product Type	Input Module
Series	VersaMax



Benefits of Automation in Industrial Setting

- · Reduced factory lead times
- Faster return on investment (ROI)
- Improved competitiveness in the market
- Consistent and enhanced part production and quality
- Smaller environmental footprint
- Improved planning capabilities
- Decreased reliance on outsourcing
- Optimal utilization of floor space

A programmable logic controller (PLC) is a highly capable solid-state control system that utilizes user-programmable memory to store instructions for executing various functions such as I/O control, logic operations, precise timing, accurate counting, three-mode (PID) control, communication protocols, arithmetic calculations, and data and file processing.

PLCs have evolved into sophisticated controllers capable of managing complex processes.

Originally designed to perform the logic functions previously carried out by electrical hardware like relays, switches, and mechanical timers/counters. They find substantial application in SCADA systems and Distributed Control Systems and are often employed as the primary controller in smaller system configurations. PLCs play an extensive role in virtually all industrial processes, offering reliable and efficient control solutions.

In the realm of programmable logic controllers, below range of offerings feature renowned global brands including Emerson, and IDEC. Introducing VersaMax Modular I/O and Control - the epitome of versatility by Emerson. This exceptional control solution is compact, cost-effective, and adaptable, serving as a compact PLC, distributed I/O, or distributed control system. With its modular and scalable design, user-friendly features, and seamless integration with open systems, VersaMax proves to be a time and cost-saving solution for machine builders and end-users alike.

The IDEC MicroSmart FC6A series is available in two types, Plus and All-in-One. The Plus type features a dual RJ45 Ethernet port and embedded web server functions, and the All-in-One type



features an embedded serial port and RJ45 Ethernet port.

Discover the exceptional IDEC FT1A SmartAXIS controllers including the special FT1A with in-built touch screen HMI, meticulously crafted to offer unique features and advanced functions, perfect for applications with limited I/O needs. Benefit from its embedded Ethernet port, Modbus TCP and RTU support, USB for data logging and program updates, and Class I Div. 2 hazardous locations compliance.

Why Choose IPD for your industrial automation and PLC needs?

- 1. Comprehensive Product Range: The collection features a comprehensive range of Industrial Automation and Programmable Controllers, to suit various applications and environments.
- 2. **Quality Assurance:** At IPD, quality is paramount. We ensure that all the range of PLCs undergo rigorous testing and adhere to international standards. This commitment to quality guarantees optimal performance, reliability, and longevity.
- 3. **Expertise and Support:** With our years of experience and in-depth knowledge, we understand the complexities of industrial automation. Our team of experts is ready to assist you in selecting the right PLC automation solution tailored to your specific requirements.

Order your programmable logic controllers from IPD and experience the transformative power of industrial automation. Browse below range of PLCs and take the first step towards streamlining your processes, increasing efficiency, and achieving unprecedented control. Contact us via 1300 556 601 to discuss your automation requirements and discover how we can be your trusted automation partner.

Technical Attributes

No. of IO 7



Physical Attributes	
Maximum Temperature (°C)	55
Minimum Temperature (°C)	0
Mounting Type	DIN Rail

Protection & Standards	
Degree of Protection	IP20

Resources	
Product catalogue (Flipbook)	Download from here