

## Product No: 1SDA073414R1

### ABB E2.2N/MS 2500 3P F HR 1SDA073414R1

#### FEATURES

- IP30 protection
- Lifting plates
- Adjustable rear terminals
- S51 250V trip indicator



#### General Information

Brand	ABB
Product Type	Non-automatic ACB
Suitable For	Distribution Board Installation
Type	Main Switch
Version	Fixed

#### Technical Attributes

Design of Control Element	Push Button
Current Type	AC
Main Circuit Electrical Connection	Bolt Connection
Maximum Operational Voltage AC (V)	690
No. of Poles	3
Power Loss (W)	267
Rated Current (A)	2500
Rated Impulse Withstand Voltage (kV)	12
Rated Insulation Voltage AC (V)	1000
Rated Operational Current AC-21A 415V (A)	2500
Rated Operational Current AC-23A 380-415V (A)	2500
Rated Operational Voltage (V)	690
Rated Short-Time Withstand Current - I <sub>cw</sub> (kA)	66
Rated Short-time Withstand Current - I <sub>cw</sub> (kA/1s)	66
Rated Short-time Withstand Current - I <sub>cw</sub> (kA/3s)	50
Rated Uninterrupted Current - I <sub>u</sub> (A)	2500
Rated Voltage (V)	690

### Technical Attributes

Terminal Type	Rear Flat Horizontal
---------------	----------------------

### Physical Attributes

Interlockable	Yes
---------------	-----

### Dimensions

Dimensions (mm)	276W x 371H x 270D
-----------------	--------------------

### Protection & Standards

Degree of Protection	IP30
----------------------	------