

CA727/2


**connectwell**  
 THE RIGHT CONNECTION

### Pre Assembled Shorting Links

Internal Shorting Link Assemblies consist of a Current Bar shorting Sleeves and Screws. They install easily into the centre of the Terminal Block and connect to the current bar. They are available as standard 2, 3, 4, 10 or 100 pole assemblies and are ready for immediate installation.

#### PRODUCT SPECIFICATION

Rated Current	32 A
Torque	0.4 Nm

#### ORDERING INFORMATION

CAT. NO.	DESCRIPTION	STD. PACK
CA727/2	Pre Assembled Shorting Link assemblies with 2 poles	100
CA727/3	Pre Assembled Shorting Links assemblies with 3 poles	100
CA727/4	Pre Assembled Shorting Link assemblies with 4 poles	100
CA727/10	Pre Assembled Shorting Links assemblies with 10 poles	10

#### SUITABLE FOR

ODL4U	4 sq.mm Offset Double Level Terminal Blocks.
ODL4UCR	4 sq.mm 2 Level Offset Corrosion Resistant Terminal Block in Grey colour
ODL4UHV	4 sq.mm Offset Double Level Terminal Blocks.
CMT4P	4 sq.mm Micro Terminal Block with Philips Head Screw.
ODL4UA	Stackable 4 sq.mm Offset Double Level Terminal Blocks.
CMT4	4 sq.mm Micro Terminal Blocks.
CDL4U(I.S)	4 sq.mm Double Level Internally Shorted Terminal Blocks.
CMB4	4 sq. mm Panel Mount Terminal Blocks.
CDL4UEN1	4 sq.mm Terminal Blocks with Neon Lamp indicator.
CDL4U	4 sq.mm Double Level Terminal Blocks.