


Product No: 271585

STAHL 6409/4148-5103-162-2220-22-850011 EMERGENCY LUMINAIRE WITH LED GRP 271585

FEATURES



- Viewing angles: 61.6 degrees (wide) to 2.5 degrees (tele)
- 30x optical zoom capability
- Full HD resolution at 1080p (1920x1080 pixels)
- Includes 1 alarm input and 1 relay output
- Operational voltage rated at 230 VAC
- Operating temperature range from -40 °C to +60 °C
- IP66 rated for dust and water resistance
- Marine certification approved

General Information

| Brand | STAHL |
|-------------|-----------|
| ProductType | Emergency |
| Series | 6409/4 |

Technical Attributes

| Application | Application range (zones) - 2, 21, 22 |
|--|---------------------------------------|
| Battery Size | 6V, 7.0Ah |
| Lamp Wattage (W) | 45 |
| No. of Lamps | 1 |
| Nominal Power (W) | 45 |
| Rated Frequency (Hz) | 50 - 60 |
| Rated Maximum Operational Voltage AC (V) | 240 |
| Rated Minimum Operational Voltage AC (V) | 110 |
| Rated Operational Voltage AC (V) | 110 -240 |

| Physical Attributes | |
|--------------------------------|------------------------|
| Ambient Temperature Range (°C) | -30 to +55 |
| CableType | Finely stranded, solid |



| Colour | Enclosure - Light Grey (RAL 7035) |
|--------------------------|---|
| Enclosure Material | Polyester resin, Glass fibre reinforced |
| Lamp Type | LED |
| LED Colour | Neutral White |
| Maximum Temperature (°C) | 50 |
| Minimum Temperature (°C) | -30 |
| Mounting Type | Surface |

| Dimensions | |
|---------------------------|-----------------------|
| Cable Cross Section (mm²) | 4 - 6 |
| Dimensions (mm) | 183.5W x 125H x 1467D |

| Protection & Standards | |
|-------------------------|-------------|
| Certifications | IECEX, ATEX |
| Degree of Protection | IP66/67 |
| Rated Impact Resistance | IK10 |
| Standards and Approvals | ATEX/IECeX |

Resources

Product catalogue (Flipbook)

Download from here