

Product No: VBC7300101

ABB VBC7-30-01-01 MINI REVERSING CONTACTOR 24 V DC – 3 NO – 0 NC – SCREW TERMINALS VBC7300101

FEATURES

- Very compact, falt design
- Easy and quick mounting in any position
- Compact reversing contactor as one module, including blocking function
- Low power consumption
- Positive linked and guided contacts
- Hum-free operating DC coil



General Information

Brand	ABB
Product Type	Mini Contactor

Technical Attributes

Actuating Voltage Type	DC
Auxiliary Contacts	1NC
Function	Reversing Contactor
Main Circuit Electrical Connection	Screw Connection
No. of Normally-closed Auxiliary Contacts	1
No. of Normally-open Contacts	3
No. of Poles	3
Operating Voltage AC (V)	690
Power Loss (W)	2.0/pole
Rated Control Circuit Voltage DC (V)	24
Rated Control Supply Voltage DC (V)	24
Rated Frequency (Hz)	50/60
Rated Impulse Withstand Voltage (kV)	6
Rated Insulation Voltage (V)	690
Rated Operational Current AC-1 240V (A)	20
Rated Operational Current AC-1 690V (A)	6
Rated Operational Power AC-3 400V (kW)	5.5
Rated Operational Power AC-3 415V (kW)	5.5

Technical Attributes

Rated Operational Voltage AC (V)	690
Terminal Type	Screw

Physical Attributes

Mounting Type	Rail Mount
Operational Temperature Range (°C)	-20 to +55

Dimensions

Dimensions (mm)	96.2W x 57.5H x 46.7D
-----------------	-----------------------

Protection & Standards

Degree of Protection	IP20
NEMA Degree of Protection	1
Pollution Degree	3

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------