


## Product No: OT1600E12P

### ABB OT1600E12P SWITCH-DISCONNECTOR OT1600E12P

#### FEATURES

- Front operated, 3 pole switch disconnecter
- Switches operating mechanism is between the poles
- Base mounted
- With black handle and shaft
- Terminal bolt kit included
- Degree of protection: Handle IP65/ Front IP00



#### General Information

Brand	ABB
Product Type	Base Mount Load Break Switch
Type	Main Switch

#### Technical Attributes

Conventional Free-Air Thermal Current - I <sub>th</sub> (A)	1600
Conventional Thermal Current - I <sub>the</sub> (A)	1600
Main Circuit Electrical Connection	Bolt Connection
Maximum Operational Voltage AC (V)	1000
Mode of Operation	Front operated
No. of Poles	3
Operating Mechanism	Mechanism Between the Poles 12
Power Loss (W)	48/Pole
Rated Impulse Withstand Voltage (kV)	12
Rated Insulation Voltage (V)	1000
Rated Operational Current AC-21A 415V (A)	1600
Rated Operational Current AC-22A 380-415V (A)	1600
Rated Operational Current AC-22A 500V (A)	1600
Rated Operational Current AC-22A 690V (A)	1600
Rated Operational Current AC-23A 380-415V (A)	1250
Rated Operational Current AC-23A 500V (A)	1250
Rated Operational Current AC-23A 690V (A)	1250
Rated Operational Power AC-23A 380-415V (kW)	710
Rated Operational Power AC-23A 400-415 V (kW)	710

### Technical Attributes

Rated Operational Power AC-23A 500V (kW)	900
Rated Operational Power AC-23A 690V (kW)	1200
Rated Operational Voltage (V)	1000
Rated Short-Time Withstand Current - I <sub>cw</sub> (kA)	50
Rated Short-time Withstand Current - I <sub>cw</sub> (kA/1s)	50
Rated Uninterrupted Current - I <sub>u</sub> (A)	1600
Terminal Type	Lug terminals

### Physical Attributes

Control Element Colour	Black
Handle Colour	Black
Handle Dimensions (mm)	308.7W x 70H x 69.4D
Handle Material	Plastic
Handle Type	Pistol
Included	Handle, Shaft
Interlockable	Yes
Mounting Type	Base Mount
Shaft Dimensions (mm)	12W x 12H x 280D
Terminal Width (mm)	50

### Dimensions

Cable Cross Section (mm <sup>2</sup> )	2 x 500
Dimensions (mm)	334.5W x 372H x 167D
Handle Length (mm)	274

### Protection & Standards

Degree of Protection - Handle	IP65
Pollution Degree	3
Standards and Approvals	IEC 60947-3

### Resources

Product catalogue (Flipbook)	<a href="#">Download from here</a>
------------------------------	------------------------------------