

Product No:101184329

SCHMERSAL ZQ900-22 PULL-WIRE EMERGENCY STOP SWITCH 101184329

FEATURES

- Pull-wire emergency stop switch
- Metal enclosure
- Switching element includes NO (Normally Open) and NC (Normally Closed) contacts with snap action
- Equipped with 1 auxiliary contact and 1 safety contact
- Screw connection terminal connector
- Thermal test current of 6 A
- Utilisation category AC-15 rated at 230 VAC, 4 A
- Utilisation category DC-13 rated at 24 VDC, 1 A
- Part of the ZQ series with an IP rating of IP65



General Information

Brand	SCHMERSAL
EAN	4030660000000
eCl@ss Number, Version 11.0	27-27-27-01
eCl@ss Number, Version 9.0	27-27-27-01
ETIM 6.0	EC001831
ETIM 7.0	EC000030
Product Type	Emergency Stop
Series	ZQ

Technical Attributes

Contact Material	Silver
Maximum Actuating Speed (m/s)	2.5
Maximum Cable Cross Section (mm ²)	2.5
Maximum Fuse Rating	10 A gG D-fuse slow blow
Minimum Cable Cross Section (mm ²)	0.25
Minimum Mechanical Life	20000000 Operations
No. of Safety Contacts	2

Rated Insulation Voltage (V)	500
Rated Short-circuit Current (A)	100
Switching Element	NO contact, NC contact
Switching Principle	Slow action
Terminal Type	Screw terminals M20 x 1.5
Utilisation Category	DC-13 AC-15

Physical Attributes

Actuator Type	Angle roller lever K230
Enclosure Material	Metal, zinc die-cast
Gross Weight (g)	2775
Maximum Ambient Temperature (°C)	80
Maximum Temperature (°C)	70
Minimum Ambient Temperature (°C)	-30
Minimum Temperature (°C)	-25
Net Weight (g)	192.32

Dimensions

Sensor Height (mm)	90
Sensor Length (mm)	14.5

Protection & Standards

Degree of Protection	IP65
Standards	EN IEC 60947-5-1 / EN ISO 13849-1 / BG-GS-ET-15

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------