

Product No:103022

DEHN TELESCOPIC LPS MAST H22.35MST/TZN C/W FLANGE 565X565MM 103022

FEATURES

- Telescopic lightning protection mast for a bucket or concrete foundation
- For protecting special facilities " such as biogas plants and free field PV systems, systems located in a hazardous area and ammunition depots " against direct lightning strikes \
- The mast for a max. gust wind speed of 194 km/h
- The masts are erected in a bucket foundation (pre-fabricated) or an on-site concrete foundation with foundation basket
- Version with flange plate for fast mounting and conical mast parts with a plug-in system, including testable statics
- Height above ground level: 13.38 m.



General Information

Accessory Type	Lightning Protection
Brand	DEHN
Model	Interception rod
Product Type	Accessory
Suitable For	Air Termination Rods

Technical Attributes

Connection Type	Round conductor
Surface Protection	Hot-dip galvanized

Physical Attributes

Material	Steel
----------	-------

Dimensions

Diameter (mm)	15
Dimensions (mm)	57W x 600H x 57D

Protection & Standards

Standards and Approvals

DIN EN 62561-(1+2), DIN EN 1991-1-4 + DIN EN 1991-1-4/NA

Resources

Product catalogue (Flipbook)

[Download from here](#)
