

## **Product No: HS6B-03B03**

## IDEC SAFTY INTERLOCK 3NC 3m CABLE SAFETY\_SWITCH HS6B-03B03

## **FEATURES**

- Integral molded cable reduces wiring time
- watertight sealing (contact is sealed; housing allows drainage)
- Direct Opening Action: Opening the door forces the contacts to disconnect even if the contacts are welded
- (IEC/ENC60947-5-1)
- Keys comply with ISO14119 and EN1088
- B10d: 2.0E+06



| General Information |                         |
|---------------------|-------------------------|
| Brand               | IDEC                    |
| Product Type        | Safety Interlock Switch |

| Technical Attributes            |         |
|---------------------------------|---------|
| Contacts                        | 3       |
| Minimum Electrical Life         | 100000  |
| Minimum Mechanical Life         | 1000000 |
| Rated Insulation Voltage (V)    | 300     |
| Rated Thermal Current - Ith (A) | 2.5     |

| Physical Attributes                |           |
|------------------------------------|-----------|
| Housing Colour                     | Black     |
| Operational Temperature Range (°C) | -25 to 70 |

| Dimensions       |                 |
|------------------|-----------------|
| Cable Length (m) | 3               |
| Dimensions (mm)  | 30W x 15H x 78D |
| Weight (g)       | 270             |



| Protection & Standards |      |
|------------------------|------|
| Degree of Protection   | IP67 |
| Pollution Degree       | 3    |

| Resources                    |                    |
|------------------------------|--------------------|
| Product catalogue (Flipbook) | Download from here |