

Product No: SL2-PSTN

NOVARIS SIGNAL LINE PROTECTOR 1 PAIR 20 KA SL2-PSTN

FEATURES

- - Plug-in signal line protector
- - Multistage protection
- - For most twisted pair signalling schemes
- - Visual indicator & Alarm contacts



General Information

Brand	NOVARIS
Product Type	Signal Line Protector

Technical Attributes

Connection Type	Series
Lightning Impulse Current (10/350 μ s) - Iimp (kA)	2.5 (5 - Common Mode)
Maximum Continuous Operating Voltage MCOV AC (V)	130
Maximum Continuous Operating Voltage MCOV DC (V)	180
Maximum Discharge Current (8/20 μ s) - I _{max} (kA)	10 (20 - Common Mode)
No. of Pairs	1
Voltage Protection Level (1kV/ μ s) - U _p (kV)	0.22 (L-L), 0.35 (L-PE)

Physical Attributes

Mounting Type	DIN Rail
Operational Temperature Range (°C)	-40 to 70

Protection & Standards

Degree of Protection	IP20
Standards and Approvals	IEC 61643-21, AS/NZS 1768, AS/NZS 4117

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------

TECHNICAL DRAWING

