

Product No: 943 940-999-004

HIRSCHMANN MANAGED RACKMOUNT SWITCH MAR1020-99 TTTTTTTTTTTTTTTTTMMMMMMMSCCHPH 943 940-999-004

FEATURES

- Ruggedized Managed Rackmount Switch
- 20 Ports with a maximum of 100 Mbit/s each
- 2 Combo Ports supporting either 2 x 10/100/1000 TX or 2 x GE SFP
- Includes 16 x 100BASE-FX MM-LC FE ports and 2 x SFP Slots for 100 Mbit/s SFP modules
- Features an additional 2 x Twisted Pair (TX) RJ45 ports with 10/100 Mbit/s connectivity
- Operating temperature range from 0 °C to +60 °C
- Dual power supply options: supports both AC (110/230 V) and DC (110/250 V)
- Layer 2 Professional network management capabilities

General Information

| Brand | HIRSCHMANN |
|--------|------------|
| Series | MAR1030 |

| Technical Attributes | |
|--|----|
| No. of 100Mb Ports | 20 |
| No. of Ethernet Ports | 16 |
| No. of Fiber Ports | 4 |
| Rated Maximum Operational Voltage DC (V) | 48 |
| Rated Minimum Operational Voltage DC (V) | 24 |

| Physical Attributes | |
|--------------------------|---------------------|
| Maximum Temperature (°C) | 60 |
| Minimum Temperature (°C) | 0 |
| Mounting Type | 19" Control Cabinet |



| Degree of Protection | IP30 |
|-------------------------|-------------|
| Standards and Approvals | IEC 61850-3 |

Resources

Product catalogue (Flipbook)

Download from here