

Product No: OT30F3

ABB SWITCH-DISCONNECTOR 3P 30A IP20 OT30F3

FEATURES

- Pole Configuration: 3P
- Operating Mode: Front Operated
- IEC 60947-3, UL 98, CSA C22.2 NO.4
- Base mount



General Information

Brand	ABB
Product Type	Main Switch

Technical Attributes

Mechanical Durability	20000
Net Weight (kg)	0.36
No. of Poles	3P
Power Loss (W)	0.7
Rated Current (A)	30
Rated Impulse Withstand Voltage (kV)	8
Rated Insulation Voltage (V)	750
Rated Operational Current AC-21A 500V (A)	40
Rated Operational Current AC-22A 500V (A)	40
Rated Operational Current AC-22A 690V (A)	40
Rated Operational Current AC-23A 500V (A)	40
Rated Operational Current AC-23A 690V (A)	40
Rated Operational Power AC-23A 500V (kW)	22
Rated Operational Power AC-23A 690V (kW)	37
Rated Operational Voltage (V)	750
Terminal Type	Screw Terminals
Tightening Torque (Nm)	6.2

Physical Attributes

Handle Type	Knob
Mounting Type	Base mounting

Dimensions

Dimensions (mm)	70W x 100H x 74D
-----------------	------------------

Protection & Standards

Degree of Protection	IP20
Pollution Degree	3
Standards	IEC 60947-3, UL 98, CSA C22.2 NO.4