


Product No: MCRA040AT1

ABB MCRA040AT1 MINI CONTACTOR RELAY 4NO 24V 50/60HZ MCRA040AT1

FEATURES

- Compact design, ideal for installations with limited space
- Convenient and secure wiring with screw terminals for ease of installation
- Suitable for residential, commercial and industrial settings
- Options for wall or rail mounting to accommodate different installations needs



General Information

Brand	ABB
Product Type	Mini Contactor Relay
Series	M

Technical Attributes

Actuating Voltage Type	AC
Auxiliary Contacts	4NO
Connection Type	Screw Connection for Auxiliary Circuit
Mode of Operation	AC
No. of Normally-open Auxiliary Contacts	4
No. of Poles	4
Operating Voltage AC (V)	690
Operating Voltage DC (V)	440
Operating Voltage Type	AC
Power Loss (W)	0.4/pole
Rated Control Circuit Voltage AC (V)	24
Rated Control Supply Voltage AC (V)	24
Rated Frequency (Hz)	50/60
Rated Impulse Withstand Voltage (kV)	6
Rated Insulation Voltage (V)	750
Rated Operational Current (A)	6
Rated Operational Current AC-15 240V (A)	6

Technical Attributes

Rated Operational Current AC-15 400V (A)	4
Rated Operational Voltage AC (V)	690
Rated Supply Voltage AC (V)	24
Short-Circuit Protective Device	10A, fuse type gG
Terminal Type	Screw

Physical Attributes

Mounting Type	DIN Rail
Operational Temperature Range (°C)	-40 to +55

Dimensions

Dimensions (mm)	45W x 48H x 56D
-----------------	-----------------

Protection & Standards

Degree of Protection	IP20
----------------------	------

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------