

Commercial product name :	Manufacturer : Isola as N-3945 Porsgrunn, Norway
Area of use : Tetningsmaterialer på rull	AVCP System : 4
Notified body :	
Product standard : EN 13859-1: Flexible sheets for waterproofing Definitions and characteristics of underlays Part 1: Underlays for discontinuous roofing	

Property	Method	Unit	Value
Tensile strength MD after artificial ageing	-	%	NPD*
Dangerous Substances	Ingen metode tilgjengelig	-	NPD*
Pliability	EN 1109	°C	≥100
Tensile strength MD	EN 12311-1	N/50 mm	485±20%
Tensile strength CMD after artificial ageing	-	%	NPD*
Elongation At Maximum Tensile Force CMD	EN 12311-1	%	38±8
Resistance to water penetration	EN 1928 (A)	-	W1
Tear resistance CMD	EN 12310-1	N	≥100
Euro fire class according to EN 13501-1	EN ISO 11925-2	-	F
Elongation At Maximum Tensile Force MD	EN 12311-1	%	33±7
Tear resistance MD	EN 12310-1	N	≥100
Tensile strength CMD	EN 12311-1	N/50 mm	340±20%

* No Performance Declared

The product properties are in conformity with the declaration of performance above.
This declaration of performance is issued under the sole responsibility of the manufacturer

Name and function	Place and date of issue	Signature
Trond Risberg Environmental- and Documentation Manager	Porsgrunn , 2020.06.24	