

# Geo6-XR GREEN

The latest innovation for installing wall and floor coverings



**Selection PRO**

**green laser**



TECHNICAL DATA		GEO6XR GREEN
Self-levelling range		± 3°
Accuracy		± 2 mm / 10 m
Laser diode / class		green / 2
Working range without receiver		40 m* (radius)
Working range with receiver		60 m** (radius)
Operating time / Power supply		
	1 x 360°	15 h / Li-Ion
	2 x 360°	7 h / Li-Ion
	3 x 360°	5 h / Li-Ion
Dust/waterprotection		IP 54
Temperature range		-10°C to +45°C
Size		115 x 96 x 118 mm
Weight (instrument with battery)		0,8 kg
		* depending on room illumination
		** depending on direction of laser

FEATURES	SUPPLIED WITH
<ul style="list-style-type: none"> <li>· 3 x 360°-Laser lines - form 6 laser crosses</li> <li>· Laser lines switchable separately</li> <li>· Plumbing function</li> <li>· Minimum laser line distance to floor 8 mm</li> <li>· Minimum laser line distance to wall 6 mm</li> <li>· Height adjustable platform from 25 to 85 mm</li> <li>· Wall-mount               <ul style="list-style-type: none"> <li>· height and side adjustable</li> <li>· can be fixed to a wall</li> <li>· Attachment to magnetic surfaces</li> <li>· strap attachment</li> </ul> </li> <li>· Visual and audible alarm when out of level</li> <li>· Self-levelling function can be locked for manual use</li> <li>· 5/8" thread for use with tripods etc. (bottom / face adaptor)</li> <li>· 1/4" thread for use with adaptor etc. (top side)</li> <li>· Use with receiver FR 75-MM / FR 55 / FR 55-M (optional)</li> </ul>	<p><b>ART.-NO. 533200</b></p> <ul style="list-style-type: none"> <li>· Li-Ion battery</li> <li>· Intelligent Charger &amp; USB 3.0 Cable</li> <li>· Battery case for alkaline batteries</li> <li>· Height adjustable platform</li> <li>· Wall-mount</li> <li>· Support rail</li> <li>· 20 mm Fixed height adaptor with 5/8"</li> <li>· 3x Height measurement pins</li> <li>· Magnetic target</li> <li>· Container</li> </ul>