

DECLARATION OF PERFORMANCE

NO: 0303

1. Identification code of the product type

0,75 mm LINEFLEX EPDM MEMBRANE

2. Type, batch or serial number or other identifying mark to identify the construction product

Batch N°. as shown on the label and on the product

3. Intended use as foreseen by the manufacturer of the construction product in accordance with the harmonised technical specification

Flexible sheets for use waterproofing and underlays for discontinuous roofing

4. Name, registered trade name or registered trade mark and contact address of the manufacturer**LINEFLEX**

AK-İZO Yalıtım Sistemleri San. Ve Tic. A.Ş.

DOSAB, Reyhan Sk., No:3, Osmangazi / BURSA / TÜRKİYE

5. Name and contact address of the authorised representative

Not relevant

6. System for assessment and verification of constancy of performance of the construction Product

System 3 / The notified body

Centrum Stavebního Inženýrství (CSI) – IN 1390

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

EN 13859-1:2010

Efectis Era Avrasya Test Laboratory / Notified Body Nr: 2184 / Accredited Body Nr: AB – 0330 - T

Reaction to Fire Classification Report No.: ERA – 14 – 131

Centrum Stavebního Inženýrství (CSI) / Notified Body Nr: 1390 / Accredited Body Nr: 1007.6

Determination Of Watertightness Test Report No.: AP492 – 05/08

8. Declared Performance

Basis Characteristics	Performance	Assessment and Verification of Constancy of Performance	Harmonized technical standards
Reaction to Fire (EN 13501-1:2007+A1:2009 and EN ISO 11925-2)	Class E	System 3	EN 13859-1:2010
Determination of Watertightness (EN 1928:2007) - Before Ageing	Class W1		
Tensile Properties			
Tensile Strength (MD*) (EN 1296 afterwards to EN 12311-1) - Before Ageing - After Ageing	NPD NPD	System 3	
Tensile Strength (CD*) (EN 1296 afterwards to EN 12311-1) - Before Ageing - After Ageing	NPD NPD		
Elongation at Break (MD*) - Before Ageing - After Ageing	NPD NPD		
Elongation at Break (CD*) - Before Ageing - After Ageing	NPD NPD		
Tear Resistance (EN 12310-1:2001) - Before Ageing - After Ageing	NPD NPD	System 3	
Determination of foldability at low temperature (EN 495-5)	-40 °C		

MD*: Machine Direction

CD*/KD*: Cross Direction

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by;

Name And Function : İskender ULUSAY/ CEO

Place And Date Of Issue : 26.05.2021

Signature :

Date : 26.05.2021