

FDV DOCUMENTATION

1190005000600

Slukmansjett Butyl 37cm x 37cm

PRODUCT DESCRIPTION

Made of Butyl Rubber & Polypropylene Spun Bonded Non Woven Fabric with Siliconised Release Paper

TECHNICAL DATA SHEET

POLYMER NAME :- BUTYL RUBBER (IIR)

Outstanding Properties	
Grade	Butyl 065
Operating Temp Range Deg C	-35 to 100
Glass Transition Temp	-66
Hardness Range Sh A	35-95
Tensile Strength (Reinforced) Mpa	<18.0
Heat Ageing Resistance	Very Good
Oxidation Resistant	Excellent
Ozone Resistance	Excellent
Sunlight Ageing Resistance	Very Good
Electrical Resistivity	Excellent
Adhesion to Metals	Good
Adhesion to Fabrics	Good
Oxygenated Solvents	Good - Very Good
Dilute Acids	Excellent
Concentrated Acids	Good
Alkalis	Excellent
Water	Very Good

Polymer Name: - Polypropylene Spun Bonded Non Woven Fabric

Thickness: 0.23±0.03 mm

GSMs (grams per square meter): 50gsm.

Color: White

Tensile Strength: 100 N

Max. Elongation: 50%

Temperature Resistance: -20°C/ +70°C

Solubility in water: Not Soluble in water

<u>SAFETY DATA SHEET</u>	
<u>According to EC Regulations 91/555/EEC</u>	
<u>IDENTIFICATION OF THE SUBSTANCE</u>	Products are made of Butyl Rubber Compound.
<u>HANDLING</u>	1. Normal handling procedure to be followed.
<u>STORAGE</u>	(i) Store product only unopened, in original packing. (ii) Open packing just before use. (iii) Protect against Moisture, Direct Sun Light, Humidity, Warming, Contamination with Dust, Oil, Grease, Acidic/Alkaline atmosphere & other Contamination to prevent possibilities of premature degradation.
<u>SELF LIFE</u>	BUTYL SEALING ROLL – 12 Months in Original Packing.
<u>TOXICOLOGICAL INFORMATION</u>	According to our experience & information the product has no harmful effects on health if properly handled.
<u>FIRE FIGHTING MEASURES</u>	
<u>1. Extinguishing Media</u>	Use an extinguishing agent suitable for surrounding fires.
<u>2. Special Protective equipment for Fire-Fighters</u>	Fire-Fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
<u>ACCIDENTAL RELEASE MEASURES</u>	
<u>1. Personal Precautions</u>	No special measures required.
<u>2. Environmental Precautions</u>	No special measures required.
<u>3. Methods for cleaning up</u>	Take up mechanically
<u>ECOLOGICAL INFORMATION</u>	The product is practically insoluble in water. In view of its consistency & insolubility in water no ecological problems are to be expected if the product is properly handled.
<u>DISPOSAL CONSIDERATION</u> (As hazardous waste)	The product is not regarded as hazardous waste as defined by EU directions.
<u>REGULATORY INFORMATION</u>	This product is not classified according to EU Registration.
Note :- In the manufacture of the product Polycyclic Aromatic Hydrocarbons (PAH) & Poly Vinyl Chloride (PVC) are not used as additives or ingredients.	

MANUFACTURER/EXPORTER:

Sakshi International

Backside G.N.E. College,
Sidhwan Canal Road, Isher Nagar,
Ludhiana-141006
Punjab INDIA

Phone: + 91-161-2495121, 2497137, 2844136, 2845136

Fax: + 91-161-2502121, 2844236

www.sakshiimpex.com

info@sakshigroup.org