




PRODUCT SPECIFICATION SHEET

Product:	FILM FACED PLYWOOD COMBI PINE/EUCALYPTUS
Producer:	<p>Tableros Ind. e Com. de Painéis LTDA          Rua Marechal Deodoro, 2081 - CEP 85555-000          Palmas, PR, Brasil  <a href="http://www.tableros.com.br">www.tableros.com.br</a></p>
Contact:	Phone: +55 46 3263-1515
Description:	<p>Film faced plywood combi, is the special plywood with two sides coated and water proof film. The film is adhesive impregnated paper with 180 gr/m<sup>2</sup>, the function of the film is to protect the inside wood from moisture, water, weather and extend the plywood's service life. Film faced plywood can be used in harsh and outside environment.</p> <p>As per customer's request, the mill can produce Anti-Slip on one side</p>
Size:	Nominal: 1.220 x 2.440 (4' x 8'), 1.250 x 2.500 or as per your requirement.
Tolerances:	Dimensional accuracy according to EN 315 / EN 324
Thickness (mm):	Nominal: 12 / 15 / 18 / 21
Plies/layers:	05 / 07 / 09
Edge:	Sealed with waterproof paint
Exposure durability:	Bond quality (class 3 phenolic) EN 314 – Panel bonded with an exterior adhesive. Panel bond classifications suitable for temporary exposure to weather. These panels are intended to resist the effects of moisture due to construction delays, high humidity, or other conditions of similar severity.
Packaging:	Units with 75 / 60 / 50 / 42 panels, with 5 across steel straps and 2 longitudinal steel straps and over 3
Warranty:	<p>16 reuses</p> <div style="display: flex; justify-content: space-around;">   </div> <div style="text-align: center; margin-top: 10px;">  </div> <p>Valid warranty against any relative manufacturing defects, the gluing of the wooden veneers that make up the panel. The warranty does not apply to Phenolic Film whose wear is variable</p>