




FSN-TPG (fermacell)



- Material: Steel
- Coating: phosphated
- Drive: Cross drive PH
- Thread: HiLo thread
- Screw head: Small countersunk head 60°
- Suitability: For gypsum fibreboard (fermacell boards) on metal profiles up to 0,7 mm in thickness without pre-drilling
- Specially: collated, belt system for strip screws




Diameter	Length	Full thread length	Head-Ø	Drive	Art. No.	Sales unit	Outer carton		GTIN (EAN Code)
d	l	lg	dk			[pcs]	[pcs]		
[mm]	[mm]	[mm]	[mm]						
3.9	19	13	6.8	PH 2	665095	1.000	8.000		40 4896 2055 184
	22	16	6.8	PH 2	665081	1.000	8.000		40 4896 2052 831
	30	24	6.8	PH 2	665098	1.000	6.000		40 4896 2055 214
	35	29	6.8	PH 2	665084	1.000	4.000		40 4896 2052 862
	45	39	6.8	PH 2	665101	1.000	4.000		40 4896 2055 245
	55	49	6.8	PH 2	665087	600	2.400		40 4896 2052 893

FSN-TPGM (fermacell)

- Material: Steel
- Coating: phosphated
- Drive: Cross drive PH
- Thread: HiLo thread
- Screw head: Small countersunk head 60°
- Suitability: For gypsum fibreboard (fermacell boards) on metal profiles up to 0,7 mm in thickness without pre-drilling
- Specially: collated, belt system for strip screws



Diameter	Length	Full thread length	Head-Ø	Drive	Art. No.	Sales unit	Outer carton		GTIN (EAN Code)
d	l	lg	dk			[pcs]	[pcs]		
[mm]	[mm]	[mm]	[mm]						
3.9	30	24	6.8	PH 2	665103	1.000	4.000		40 4896 2196 665
	45	39	6.8	PH 2	665104	1.000	4.000		40 4896 2196 672