

**Product:**

**Jøtul F 171, F 174, F 176  
ZENSORIC**



**Room heater fired by solid fuel**

**DoP: F170-CPR-280423**

Standard: EN 13240:2001/A2:2004:AC:2007

Minimum distance to adjacent combustible materials : SIDE 550 mm  
Minimum distance to adjacent combustible materials : REAR 50 mm (225 mm - without insulated flue connector)  
Minimum distance to adjacent combustible materials : FLOOR - see manual  
Minimum distance to adjacent combustible materials : FRONT 1100 mm

Emission of CO in combustion products (13% O<sub>2</sub>) : 887 mg/Nm<sup>3</sup>  
Emission of OGC in combustion products (13% O<sub>2</sub>) : 38 mgC/Nm<sup>3</sup>  
Emission of NO<sub>x</sub> in combustion products (13% O<sub>2</sub>) : 99 mg/Nm<sup>3</sup>  
Emission of PM in combustion products (13% O<sub>2</sub>) : 30 mg/Nm<sup>3</sup>  
Flue gas temperature : 287 °C  
Nominal heat output : 5 kW  
Efficiency : 76%  
Fuel type : Wood  
Operation type : Intermittent  
Electrical safety : -

The appliance can be installed in a shared flue.

Country	Classification	Standard	Approved by
EUR	Intermittent	EN 13240	Danish Technological Institute

Follow user's instructions. Use only recommended fuels.  
Montage- und Bedienungsanleitung beachten.  
Verwenden Sie nur empfohlenen Brennstoffen.  
Respectez les consignes d'utilisation. Utilisez uniquement les combustibles recommandés.

10083531-P01



Read instructions for further information.

Lot no: 000000 2022

Pin:000

Manufacturer:

Jøtul AS, POB 1411, N-1602 Fredrikstad, Norway