



Universalspiker til innvendig bruk.



[NO-DoP-h19/0003](#)

## EGENSKAPER



**BRIGHT**

**INDOOR**

### Fordeler:

- Flatt hode
- 40 graders diamant spids
- Firkantet stamme



## ANVENDELSE

### Bruksområde:

- Tre til tre

TEKNISK DATA

Product dimensions



Art. nr.	Item code	NOBB nr.	Fastener dimensions [mm]					
			d	l	d <sub>h</sub>	l <sub>g</sub>	t <sub>fix</sub>	bit
FIRKSQU2.0x50	FIRKSQU	55837320	2	50	11.5	-	-	-
FIRKSQU2.2x55	FIRKSQU	55837297	2.2	55	11.5	-	-	-
FIRKSQU2.5x65	FIRKSQU	55837335	2.5	65	6	-	-	-
FIRKSQU2.8x75	FIRKSQU	55837301	2.8	75	6.8	-	-	-
FIRKSQU3.4x95	FIRKSQU	55837316	3.4	95	7.6	-	-	-

Product characteristic properties

Art. nr.	Product characteristic properties					
	Characteristic Yield Moment – M <sub>y,k</sub> [M <sub>y,k</sub> ] [Nm]	Characteristic withdrawal parameter - f <sub>ax,k,90°</sub> [f <sub>ax,k,90°</sub> ] [N/mm <sup>2</sup> ]	Characteristic head pull-through parameter - f <sub>head,k</sub> [f <sub>head,k</sub> ] [N/mm <sup>2</sup> ]	Characteristic tensile capacity - f <sub>tens,k</sub> [f <sub>tens,k</sub> ] [kN]	Characteristic torsional strength - f <sub>tor,k</sub> [f <sub>tor,k</sub> ] [Nm]	Torsional ratio
FIRKSQU2.0x50	-	-	-	-	-	-
FIRKSQU2.2x55	-	-	-	-	-	-
FIRKSQU2.5x65	3.3	2.5	8.6	-	-	-
FIRKSQU2.8x75	4.3	2.5	8.6	-	-	-
FIRKSQU3.4x95	7	2.5	8.6	-	-	-

