

# **Product Description**

The Peltor Optime I range passive earmuffs are available in headband, neckband, foldable or helmet mounted version. These products are designed to provide moderate level of attenuation that meets the needs of the majority of industrial applications.

Technical Datasheet Peltor™ Optime™ I

When correctly selected and worn these products help reduce exposure to hazardous levels of noise and loud sounds.

The helmet mounted version is designed to fit a wide range of industrial safety helmets (see below for further details).

NOTE: A high visibility version is also available

## **Key Features**

- Modern, stylish slim line cup design
- Liquid sealing rings for improved comfort
- Unique low profile headband design helps maintain constant pressure thus providing confidence in protection
- Large space inside cup helps reduce moisture and heat build-up
- Soft wide cushions helps reduce pressure around the ears and improves comfort and wearability
- Easy to replace cushions and inserts helps keep them hygienically clean
- Easy to understand attenuation symbol to help ensure correct product selection
- Helmet mounted version fits directly to many industrial safety helmets without the need for an adapter

Helmet Manufacturer	Model	Combination size range according to EN352-3				
		P3 Adaptor	H510 (Optime I)			
3M	1465	E	NL			
Auboueix	Brennus	F	SNL			
Auboueix	Fondelec	F	SNL			
Auboueix	Iris	E	NL			
Auboueix	Iris 2	E	NL			
Sofop Taliaplast	Oceanic	E	NL			
Sofop Taliaplast	Opus	E	NL			
Berendsen Safety	Balance HD	N	SNL			
Centurion	1125/ARCO Plus	Н	SNL			
Centurion	1100/ARCO Type 2	Н	SNL			
Centurion	1540/ARCO	А	NL			
Evert Larsson	Robust	E	SNL			
Evert Larsson	Balance	E	NL			
Evert Larsson	Balance AC	E	NL			
Kemira	Тор Сар	A	SNL			
LAS	LP2002	E	SNL			
LAS	LP2006	E	SNL			
MSA	Super V-Gard	E	SNL			
MSA	V-Gard	E	SNL			
Peltor	G2000	K,E	SNL			
Peltor	G22 (Basic Set)	E	SNL			

#### Helmet mounted approved combination:

Helmet Manufacturer	Model	Combination size range according to EN352-3			
		P3 Adaptor	H510 (Optime I)		
Peltor	G3000	E	SNL		
Petzl	Vertex	E	SNL		
Protector	Style 300*	E	SNL		
Protector	Style 600	G	SNL		
Protector	Tuffmaster II	E,G	NL		
Romer	Bravo 2 Nomaz	В	SNL		
Romer	Marcus Top 2 Atlas Nomaz	В	SNL		
Romer			SNL		
Romer	Profi Expo	E	SNL		
Romer	Profi Nomaz	E	SNL		
Romer	Top Expo Atlas	В	SNL		
Schuberth	BEN	BB	SNL		
Schuberth	BER80/WPC80	EA	SNL		
Schuberth	BER S	E	SNL		
Schuberth	BOP R	В	SNL		
Schuberth	PIONIER	В	SNL		
Schuberth	SH91/WP91	EB	SNL		
Schuberth	SW1	EB	NL		
Uvex	Airwing	E	SNL		
Voss	Inap 88	E	SNL		
Voss	Inap Master	E	NL		
Voss	Inap Star	E	NL		
Voss	Inap PCG	G	NL		

\*Protector Style 300 includes all 300-versions of this helmet.





# Applications

The Peltor Optime I range earmuffs are ideal for protection against noise arising from a wide range of applications in the workplace and leisure activity. Examples of typical applications include:-

Technical Datasheet Peltor<sup>™</sup> Optime<sup>™</sup> I

- Agriculture
- Automotive
- Chemical & pharmaceutical manufacture
- Construction
- Light engineering
- Metal processing
- Woodworking

## Standard & Approval

The Peltor Optime I range earmuffs are tested and CE approved against the European Standard EN352-1:1993 (headband, neckband and foldable version) and EN352-3: 2002 (helmet mounted version). These products meet the Basic Safety Requirements as laid out in Annex II of the European Community Directive 89/686/EEC. These products have been examined at the design stage by the Finnish Institute of Occupational Health (FIOH), Topeliuksenkatu 41aA, FIN-00250 Helsinki, Finland (Notified Body number 0403) and INSPEC International Limited, 56 Leslie Hough Way, Salford, Greater Manchester M6 6AJ, UK (Notified Body number 0194).

#### Materials

The following materials are used in the manufacture of this product.

	Component	Material
	Headband/Neckband/Foldable	Stainless Steel Wire, PVC, Acetal
Headband, Neckband and	Headband padding	PVC
Foldable version	Cups	ABS
	Inserts	Polyether
	Cushions	Polyether
	Cushion cover	PVC
	Helmet attachment arm	Stainless Steel Wire, PVC, Acetal, Polyamid
	Cups	ABS
Helmet mounted version	Inserts	Polyether
	Cushions	Polyether
	Cushion cover	PVC

# Attenuation values

## Optime I Head Band Version (H510A)

Frequency (Hz)	63	125	250	500	1000	2000	4000	8000
Mf (dB)	14.1	11.6	18.7	27.5	32.9	33.6	36.1	35.8
sf (dB)	4.0	4.3	3.6	2.5	2.7	3.4	3.0	3.8
APVf (dB)	10.1	7.3	15.1	25.0	30.1	30.2	33.2	32.0
SNR = 27dB H = 32dB M = 25dB L = 15dB								



#### **Optime I Neck Band Version (H510B)**

Frequency (Hz)	63	125	250	500	1000	2000	4000	8000
Mf (dB)	13.3	10.9	17.1	25.4	31.5	32.6	36.3	34.8
sf (dB)	4.1	3.5	2.8	1.8	2.6	4.3	3.4	3.6
APVf (dB)	9.1	7.3	14.3	23.6	28.9	28.3	32.9	31.1



Technical Datasheet Peltor<sup>™</sup> Optime<sup>™</sup> I

#### **Optime I Foldable Version (H510F)**

Frequency (Hz)	63	125	250	500	1000	2000	4000	8000
Mf (dB)	14.6	12.2	18.7	27.1	32.9	35.0	36.5	34.4
sf (dB)	3.8	3.4	3.2	3.0	2.1	4.0	2.9	3.9
APVf (dB)	10.8	8.7	15.5	24.1	30.8	31.0	33.6	30.6

SNR = 28dB

H = 32dB M = 25dB L = 16dB

# Optime I Helmet Mounted Version (H510P3)

Frequency (Hz)	63	125	250	500	1000	2000	4000	8000
Mf (dB)	13.1	11.2	13.4	26.9	33.9	32.0	33.5	36.9
sf (dB)	2.3	2.0	1.9	1.8	1.9	2.4	1.8	1.8
APVf (dB)	10.8	9.2	11.5	25.1	31.9	29.6	31.7	35.1
SNR = 26dB H = 32dB M = 23dB L = 15dB								









## **Accessories/Replacement Parts**

The cushions and inserts on the Optime I range can be replaced with the HY51 Hygiene Kit for improved comfort and reassured protection.

echnical Datasheet Peltor<sup>™</sup> Optime<sup>™</sup> I

The HY100A and HY100A-01 Hygiene Pads can be placed on the cushions to help absorb moisture and sweat.

#### Key

APVf = Assumed Protection Value

Mf = Mean attenuation value

sf = Standard deviation

H = High-frequency attenuation value (predicted noise level reduction for noise with  $L_C - L_A = -2dB$ )

M = Medium-frequency attenuation value (predicted noise level reduction for noise with  $L_C - L_A = +2dB$ )

L = Low-frequency attenuation value (predicted noise level reduction for noise with  $L_C - L_A = +10$ dB)

SNR = Single Number Rating (the value that is subtracted from the measured C-weighted sound pressure level,  $L_C$  in order to estimate the effective A-weighted sound pressure level inside the ear).



#### 3M a/s Sikkerhedsprodukter

Fabriksparken 15 DK-2600 Glostrup Telefon: 43 48 01 00 Fax: 43 96 85 96 E-mail: 3msikkerhed@mmm.com www.3Msikkerhed.dk

